

MS12/MS13 - 21 sqm

Mobile LED Screen



Safety

All our Mobile LED Screens

- are built and approved according to TÜV regulations
- have all required construction books/"Baubücher"
- are approved to be used up to wind speeds of 20 m/s or 72 km/h
- have multiple safety lock systems for the hydraulic system
- are equipped with dual video processors linked in a redundant system

Add ons

Please contact us for further information about Digital Banners, Info Channels etc.



Technical Specifications

Technical Specifications	
Container Screen	
Display size:	21 m ²
Display dimensions:	W: 6000 H:3500 mm
Display resolution:	W: 1536 H: 896 px
Picture format:	16:9
Pixel pitch:	3,9 mm
Brightness:	5000 nits
Viewing angle:	H: 120° V: 75°
Screen rotation:	360°
Min. rotation space from trailer body (each side):	1400 mm
Input signals:	CVBS, SDI, HDSDI, DVI
Trim height:	2440 - 3990 mm
Built in studio:	No
Built in generator:	18 kVA
Running time generator:	11 h
External power connector:	32 A, 3 phase, 400V, CEE
Power consumption (max):	29 A
Container on ground dimensions:	L: 5000 W: 2550 H: 2440 mm
Ground space outriggers when rigged,:	L: 5000 W: 3000 mm
Weight, container on ground:	5500 kg
Trailer	
Trailer dimensions with one container:	L: 7000 W: 2550 H: 3440 mm
Weight, container on trailer:	9600 kg
Truck	Front & Back (Tool Required)
Truck dimensions with one container:	L: 7500 W: 2550 H: 3440 mm
Length, total (truck & trailer):	14300 mm
Weight, total (truck, trailers with containers):	22300 kg
Weight, truck with container:	13200 kg